



Model 80 QNIL 80 kW Natural Gas\ LP Generator Set

Generator Set Rating

Three Phase 60 Hz 50 Hz
 kW/KVA kW/KVA

Continuous
Standby 150°C 80/100 72/90
Prime Power 105°C 72/90 65/81

Single Phase 60 Hz 50 Hz
 kW/KVA kW/KVA

Continuous
Standby 150°C 54/54 58/58
Prime Power 105°C 46/46 54/54

60 Hz Sound levels @ 23 ft. (7m)


No load 68 dBa
Full load 70 dBa

Quality Power Producing Equipment

is our business at Elliott MagneTek Power Systems, Inc.. Our power systems offer solutions to requirements for reliable, quality electrical power.

- 100% full load tested.
- Performance supported by prototype testing.

- 12 lead re-connectable AC synchronous generators.
- Solid state automatic voltage regulator.
- 50 or 60 Hz operational.
- Standard Digital Control Panel meeting standards set by NFPA-110.



Product Features

System Reliability and Longevity

begin with design experience and integrity. EMPS was formed by two companies with over one hundred years experience producing state-of-the-art power generation equipment. This experience is designed into our generator sets.

Single Source Responsibility:

Product service, support and parts available through EMPS network of distributors.

Accessories and Flexibility

are designed into EMPS' generator sets at the factory level to meet specific application needs.

Organizational Commitment

to innovative, leading edge technology and environmentally friendly electrical products and services.

Generator Set Design Features

Model 80 QN\ L 80 kW NG\ LP Generator Set

Standard Equipment

- * 4 Cycle engine.
- * AC synchronous 12 lead re-connectable brushless alternator.
- * Steel base with vibration isolators between engine, generator and base.
- * Generator mounted terminal and meter /control box.
- * Circuit breaker-mounting provisions.
- * Connection area for main AC terminals and all control wiring
- * 12 volt DC engine electrical system.
- * 12 volt starter motor.
- * Battery charging alternator.
- * Battery rack and cables.
- * Flexible fuel lines.
- * Most metallic parts incorporate our powder paint primer base coat with UV inhibitive enamel top coat.
- * Single stage dry type air cleaner.
- * Corrosion resistant hardware.
- * Oil drain extension plumbed to base rail for convenient connection.
- * Microprocessor based auto start meter/ control panel.
- * Digital read out control system rated to operate from -30° C to 75° C with the following standard displays, shown continuously:
 - ** Generator AC voltage.
 - ** AC amperage:
 - Phase 1-2
 - Phase 2-3
 - Phase 3-1
 - ** Frequency
 - ** Oil Pressure
 - ** Engine Temperature
 - ** Battery Voltage
 - ** Fuel Level (Diesel Only)
- * The following can be displayed using the scroll lock function:
 - ** Run time
 - ** Safety set point for over speed
 - ** Over crank
 - ** High water temperature
 - ** Low oil pressure
- * Voltage adjust rheostat
- * Auto/off /run switch

Generator Specifications

Manufacturer: MagneTek

Insulation: The main stator, main rotor, exciter stator and exciter rotor are all insulated with Class H materials and rated Class F per NEMA MG1 -1.65 and 852757 definition. All materials are non-hygroscopic to prevent fungus growth. A polyester and epoxy combination offers maximum environmental protection.

Main Stator: 2/3 pitch and one slot skewing minimize voltage harmonics and meets telephone influence factor (TIF) per NEMA MG1-22.43. Twelve lead re-connectable design. Coated with anti-abrasive sealer.

Main Rotor: Four pole single piece lamination with full amortisseur windings and coil supports. Winding is precision wet layer wound with epoxy resin and dynamically balanced to two mil in two planes. Production over speed tested at 125% for 15 minutes. All materials are non-hygroscopic to prevent fungus growth.

Exciter: Brushless, three phase, six-pole rotor, and production over speed tested at 125% operating speed.

Rotating Diode: Sealed full wave with metal oxide surge suppressor

Bearing: Double-sealed, permanently lubricated, 50,000 hour B-10 life including magnetic pull.

Drive Coupling: Positive alignment, flexible drive discs.

Automatic Voltage Regulator Specifications

Operation: Volts per hertz, three phase sensing with overload and loss of sensing protection.

Construction: Solid state, modular: fully sealed and potted design provides component protection from corrosive environments and vibration.

Voltage Regulation: +/- 1% voltage regulation no load to full rated load: +/- 1/2% voltage regulation at steady state conditions.

Radio Interference (RFI): Integral filter provides suppression of conducted electromagnetic interference to levels meeting most commercial requirements.

Voltage Selections and Full Load Amperages at Standby Rating

Three Phase

60 Hz Amperage	50 Hz Amperage
120/208 278	110/190 273
120/240 241	120/208 250
277/480 120	230/400 130
347/600 96	240/415 125

*Single Phase

60 Hz Amperage	50 Hz Amperage
120/240 225	

Technical Specifications

Model 80 QN\ L 80 kW NG\ LP Generator Set

Engine Specifications

Manufacturer	General Motors	
Model	7.4 L(T)	
Aspiration	Turbo	
Cylinders	V-8	
Displacement	454 In ³ . (7.4 L)	
Bore and Stroke,	4.25 in x 4 in.	
	(108 mm x 101.6 mm)	
Compression Ratio	8.9:1	
Minimum C.C.A. at 5°C	750	
RPM	1800 rpm	1500 rpm
BHP Minimum REQ'D		
at Rated kW	118	106
BMEP	124 psi	123 psi

Generator Set Deration Factors

Temperature:
 1% for every 10° F above 120° F
 1% for every 6°C above 49°C

Altitude
 2% for every 1000 feet above
 Sea Level
 2% for every 305 meters above
 Sea Level

Cooling System

High Ambient 117°F (47°C) System
 Coolant Capacity with Radiator
 8 US Gal. (30.3 L)

Maximum restriction on discharge side of radiator
 1.75 In wc (.44 Pa)

	1800 rpm	1500 rpm
Coolant Flow		
	40 GPM (151 LPM)	33 GPM (125 LPM)
Heat Rejection to Coolant at Rated		
Full Load	6400 Btu/min (675.2 MJ/min)	5600 Btu/min (590.8 MJ/min)
Nat. Gas		

Heat Rejection to Coolant at Rated
 Full Load 6400 Btu/min
 Propane (675.2 MJ/min) 5600 Btu/min
 (590.8 MJ/min)

Heat Rejection to Room at Rated
 Full Load 19200 Btu/min
 Nat. Gas (2025 MJ/min) 16800 Btu/min
 (1772 MJ/min)

Heat Rejection to Room at Rated
 Full Load 19200 Btu/min
 Propane (2025 MJ/min) 16800 Btu/min
 (1772 MJ/min)

Air System

	1800 rpm	1500 rpm
Maximum Air Intake Restriction	12 In wc (2.99 kPa)	12 In wc (2.99 kPa)
Radiator Cooling Air Flow	11500 cfm (351m ³ /min)	9600 cfm (293 m ³ /min)
Combustion Air Flow	230 cfm (6.5 m ³ /min)	185 cfm (5.2 m ³ /min)
Generator Cooling Air Flow	2348 cfm (66.4 m ³ /min)	1957 cfm (55.4 m ³ /min)

Exhaust System

Exhaust Outlet Connection
 Maximum Allowable Back Pressure
 1.5 In Hg (5.08 kPa)

Exhaust Gas Flow at Standby Rating
 745 cfm (21.1 m³/min) 620 cfm (17.5 m³/min)

Exhaust Temp at Standby Rating
 1325°F (718°C) 1270°F (688°C)

Fuel System

Consumption at Standby Rating:

		Propane	Natural Gas
	kW	lbs./hr.(kg./hr.)	CFH(m ³ /hr.)
1/4	20	27.9(12.7)	551(15.6)
1/2	40	45.3(20.5)	713(20.2)
3/4	60	50.1(22.7)	896(25.4)
Full	80	54.7(24.8)	1080(30.6)

Load **1500 RPM**

		Propane	Natural Ga
	kW	lbs./hr.(kg./hr.)	CFH(m ³ /hr.)
1/4	18	22.1(10.0)	443(12.5)
1/2	36	28.6(13.0)	574(16.2)
3/4	54	35.9(16.3)	721(20.4)
Full	72	43.3(19.6)	869(24.6)

Governor Type Isochronous
 Governor Regulation: 1/4 % Steady State

Generator

Manufacturer Model	MagneTek MTG32
Motor Starting KVA, 240/480 Volt WYE at 35% Voltage Dip,100% Voltage Recovery	175 SKVA
Maximum Motor Starting KVA,35% Voltage Dip Oversized Generator MTG41	346 SKVA

Reactances

	480 V	400 V
at 105°C rise Synchronous Xd	60Hz 3.74	50Hz 3.6
Direct Axis Transient X'd	.298	.286
Direct Axis Subtransient X'd	.204	.196
Negative Sequence X ₂	.214	.205
Zero Sequence X ₀	.0032	.0031

Lubrication System

Engine Oil Capacity with Filters 8qts. (7.6 L)
 Oil Filter Type Spin On

Model 80 QN\ L

80 kW NG\ LP Generator Set

Options:

Generator

- * Upsized
- * Tropical winding protection
- * Space heater
- * Series boost
- * UL listed mainline circuit breaker

Control

- * Remote alarm annunciator
- * Emergency stop
- * Multi-point dry contact board.
- * NFPA 110 Compliance
- * Low Temperature Display Heater

Engine

- * Battery/Battery heater
- * Battery charger
- * Engine pre-heater
- * Fuel/ water separator


Generator Set

- * EMPS automatic transfer switch
- * Industrial silencer
- * Residential silencer
- * Critical silencer
- * Weather protective enclosure
- * Sound attenuation

DOOR SWING:
ENGINE DOOR: 40.75
SECURITY DOOR: 45.75

MACHINE WEIGHT:
ENCLOSED DRY WEIGHT 4032 LBS [1829 KG]

NOTES:
PRELIMINARY DRAWING DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE.



58 Elliott Power Drive
P.O. Box 403
Lexington, TN 38351
Tel: 901-967-9393
Fax: 901-968-0161

Distributed by:



All specifications subject to change without notice. Printed in the USA

Updated 2/00